

INSTALLATION INSTRUCTIONS FOR 1290

For Wall Mount Fixture

©Minka Lighting, Inc.

This product is protected by United States Federal and/or State Law, including Patent and/or Copyright laws.

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .

MOUNTING THE FIXTURE

Installation (see fig.1)

1. Disconnect power at main electrical panel before installation.
2. Thread the nipple part way into the center hole of the crossbar and secure with hex nut.
3. Attach the crossbar to the junction box using two junction box screws. The side of the crossbar marked "GND" must face out.
4. Follow wiring instructions carefully (see fig.2)
5. Place the fixture body (C) over the nipple, then tighten it with the ball nut (B).
6. Place the tube (A) over the socket of the fixture body (C).
7. Hang the finial (D) to the fixture body (C).
8. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**

Wiring (see fig.2)

1. Connect the electrical wires as follows. Connect the Black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connects fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the crossbar.
2. Tuck the wire connections neatly into the wall junction box.

Fig.1




Fig.2

